

* DE MUNICIONES PARA RIFLES | TABLAS BALÍSTICAS

CALIBRE	REF	BALA	PESO		CXP (*)	OM	VELOCIDAD (M/S)			POTENCIA (JULIOS)			RAS ANTE (CM)		
			GR	G			100M	200M	300M	OM	100M	300M	50M	100M	300M
METRICS CALIBRES															
7X64	CM7641	POWER POINT®	164	10.5	2	841	783	727	674	3.715	3.219	2.382	-	6.1	-24.4
8x57JRS	CM857JS	POWER POINT®	195	12.6	2	725	659	596	536	3.324	2.741	1.818	-	0.0	-65.0
9.3X62	CM9362	POWER POINT®	286	18.5	3	719	651	587	527	4.794	3.932	2.575	-	0.0	-66.8
9.3X74R	CM9374R	POWER POINT®	286	18.5	3	719	651	587	527	4.794	3.932	2.575	-	0.0	-66.8
22 HORNET															
22Hornet	CX22H1	SOFT POINT	45	2.92	1	820	622	458	344	980	565	172	0.0	0.0	-79.5
22Hornet	CX22H2	HOLLOW POINT	46	2.98	1	820	622	458	344	1.002	578	176	0.0	0.0	-79.5
22-250 REMINGTON															
22-250Rem	CSBST22250	BALLISTIC SILVERTIP®	50	3.24	1	1.161	1.018	890	773	2.184	1.680	968	-1.0	0.0	-18.5
22-250Rem	CX222501	POINTED SOFT POINT	55	3.56	1	1.122	956	810	677	2.243	1.628	818	-1.0	0.0	-23.1
222 REMINGTON															
222Rem	CX222R	POINTED SOFT POINT	50	3.24	1	957	793	647	518	1.483	1.020	435	-0.5	0.0	-38.9
223 REMINGTON															
223Rem	CSBST223B	BALLISTIC SILVERTIP®	55	3.56	1	988	875	771	675	1.738	1.364	812	-0.8	0.0	-27.7
223Rem	CX223LF	POWER CORE 95/5™	64	4.15	1	920	805	699	601	1.757	1.344	748	-0.5	0.0	-34.8
223Rem	CX223R	POINTED SOFT POINT	55	3.56	1	988	837	702	581	1.738	1.249	601	-0.8	0.0	-32.8
243 WINCHESTER®															
243Win	CSBST243A	BALLISTIC SILVERTIP®	95	6.16	2	945	870	800	735	2.740	2.331	1.661	-0.8	0.0	-26.9
243Win	CSBST243	BALLISTIC SILVERTIP®	55	3.56	1	1.192	1.065	949	843	2.531	2.019	1.266	-1.0	0.0	-16.0
243Win	CX243WLF	POWER CORE 95/5™	90	5.83	2	945	862	784	710	2.603	2.165	1.468	-0.8	0.0	-27.9
243Win	CX2432BP	POWER MAX®	100	6.48	1	902	825	753	684	2.637	2.207	1.516	-0.5	0.0	-31.0
243Win	CX2432	POWER POINT®	100	6.48	2	902	822	746	675	2.637	2.190	1.476	-0.5	0.0	-31.5
243Win	CX2431	POINTED SOFT POINT	80	5.18	1	1.021	901	790	689	2.702	2.103	1.228	-1.0	0.0	-17.5
6.5x55 SWEDISH															
6.5x55Swd	CX6555	SOFT POINT	140	9.07	2	777	719	663	610	2.741	2.347	1.689	0.0	0.0	-42.9
270 WINCHESTER®															
270Win	CSXP270W	XP3®	150	9.72	2/3	899	842	787	735	3.929	3.446	2.625	-0.5	0.0	-28.7
270Win	CS270WET	E-TIP®	130	8.42	2	930	866	805	747	3.640	3.158	2.348	-0.5	0.0	-26.9
270Win	CS270CT	ACCUBOND®	140	9.07	2	899	839	780	725	3.667	3.189	2.382	-0.5	0.0	-29.2
270Win	CSBST270	BALLISTIC SILVERTIP®	130	8.42	2	930	862	798	736	3.640	3.131	2.285	-0.5	0.0	-27.2
270Win	CX270WLF	POWER CORE 95/5™	130	8.42	2/3	933	852	775	703	3.663	3.056	2.083	-0.5	0.0	-28.7
270Win	CX2705BP	POWER MAX®	130	8.42	2	933	847	767	691	3.663	3.022	2.009	TBD	-	-
270Win	CX2704	POWER POINT®	150	9.72	2	869	788	712	640	3.667	3.018	1.990	-0.5	0.0	-35.1
270Win	CX2705	POWER POINT®	130	8.42	2	933	854	780	710	3.663	3.074	2.122	-0.5	0.0	-28.5
270 WINCHESTER® SHORT MAGNUM															
270WSM	CSXP270S	XP3®	150	9.72	2/3	951	892	835	781	4.396	3.864	2.961	-0.8	0.0	-24.9
270WSM	CS270SET	E-TIP®	130	8.42	2	998	931	867	806	4.198	3.651	2.739	-0.8	0.0	-22.4
270WSM	CS270WSMCT	ACCUBOND®	140	9.07	3	975	911	850	792	4.317	3.768	2.843	-0.8	0.0	-23.6
270WSM	CSBST2705A	BALLISTIC SILVERTIP®	150	9.72	2	951	891	833	778	4.396	3.857	2.945	-0.8	0.0	-24.9
270WSM	CSBST2705	BALLISTIC SILVERTIP®	130	8.42	2	998	927	860	795	4.198	3.619	2.663	-0.8	0.0	-22.6
270WSM	CX2705BP	POWER MAX®	130	8.42	2	998	908	824	745	4.198	3.475	2.339	TBD	-	-
270WSM	CX270WSM	POWER POINT®	150	9.72	2	960	874	793	716	4.480	3.711	2.493	-0.8	0.0	-26.9
7MM REMINGTON															
7 mmRem	CSXP7RM	XP3®	160	10.37	2/3	899	843	789	738	4.191	3.685	2.820	-0.5	0.0	-28.7
7 mmRem	CS7MMCT	ACCUBOND®	160	10.37	3	899	843	789	738	4.191	3.685	2.820	-0.5	0.0	-28.7
7 mmRem	CSBST7	BALLISTIC SILVERTIP®	150	9.72	2	945	885	827	772	4.339	3.804	2.896	-0.8	0.0	-25.4
7 mmRem	CX7MMRMLF	POWER CORE 95/5™	140	9.07	2/3	945	874	807	742	4.050	3.464	2.499	-0.8	0.0	-26.7
7 mmRem	CX7MMR2	POWER POINT®	175	11.34	3	872	806	743	684	4.309	3.684	2.649	-0.5	0.0	-32.5
7 mmRem	CX7MMR1BP	POWER MAX®	150	9.72	2	942	867	796	729	4.312	3.653	2.582	-0.8	0.0	-27.2
7 mmRem	CX7MMR1	POWER POINT®	150	9.72	2	942	863	789	718	4.313	3.620	2.506	-0.8	0.0	-27.7
7MM WINCHESTER® SHORT MAGNUM															
7 mmWSM	CX7MMWSMBP	POWER MAX®	150	9.72	2	975	899	826	757	4.623	3.924	2.786	-0.8	0.0	-24.9
280 REMINGTON															
280Rem	CSBST280	BALLISTIC SILVERTIP®	140	9.07	2	927	866	809	753	3.894	3.404	2.573	-0.5	0.0	-26.7