

.270 Win.							
Index No.	Wt. (grs.)	Bullet Style		Primer No.	Barrel Length		
R270W1	100	Pointed Soft Point		9 1/2	24"		
R270W2	130	Pointed Soft Point Core-Lokt™		9 1/2	24"		
R270W3	130	Bronze Pointú		9 1/2	24"		
PRSC270WA	130	Swiftú Sciroccoú		9 1/2	24"		
R270W4	150	Soft Point Core-Lokt™		9 1/2	24"		
RS270WA	140	Swift A-Frameú PSP		9 1/2	24"		
PRB270WA	140	Pointed Soft Point, Boat Tail		9 1/2	24"		
PRT270WB	140	Nosler™ Ballistic Tip™		9 1/2	24"		
PRP270WD	150	Nosler™ Partition™		9 1/2	24"		
Velocity (ft./sec.)							
Cartridge	Muzzle	100 yds.	200 yds.	300 yds.	400 yds.	500 yds.	
100 PSP	3320	2924	2561	2225	1916	1636	
130 PSPCL	3060	2776	2510	2259	2022	1801	
130 BP	3060	2802	2559	2329	2110	1904	
130 SS	3060	2838	2627	2425	2232	2048	
150 SPCL	2850	2504	2183	1886	1618	1385	
140 SAFPSP	2925	2652	2394	2152	1923	1711	
140 PSPBT	2960	2749	2548	2355	2171	1995	
140 NBT	2960	2754	2557	2366	2187	2014	
150 NP	2850	2652	2463	2282	2108	1942	
Energy (ft.-lbs.)							
Cartridge	Muzzle	100 yds.	200 yds.	300 yds.	400 yds.	500 yds.	
100 PSP	2448	1898	1456	1099	815	594	
130 PSPCL	2702	2225	1818	1472	1180	936	
130 BP	2702	2267	1890	1565	1285	1046	
130 SS	2702	2325	1991	1697	1438	1211	
150 SPCL	2705	2087	1587	1185	872	639	
140 SAFPSP	2659	2186	1782	1439	1150	910	
140 PSPBT	2723	2349	2018	1724	1465	1237	
140 NBT	2724	2358	2032	1743	1487	1262	
150 NP	2705	2343	2021	1734	1480	1256	
zeroShort-Range Trajectory *							
Cartridge	50 yds.	100 yds.	150 yds.	200 yds.	250 yds.	300 yds.	
100 PSP	-0.1	0.5	zero	-1.6	-4.6	-9.1	
130 PSPCL	0.1	0.6	zero	-1.8	-5.1	-9.8	
130 BP	-0.1	0.6	zero	-1.8	-4.9	-9.5	
130 SS	zero	0.6	zero	-1.7	-4.7	-9.0	
150 SPCL	0.3	0.8	zero	-2.4	-6.7	-13.0	
140 SAFPSP	0.2	0.7	zero	-2.1	-5.6	-10.9	
140 PSPBT	0.1	0.6	zero	-1.9	-5.1	-9.7	
140 NBT	0.1	0.6	zero	-1.9	-5.0	-9.7	
150 NP	0.2	0.7	zero	-2.0	-5.5	-10.5	
Long Range Trajectory *							
Cartridge	100	150	200	250	300	400	500

	yds.	yds.	yds.	yds.	yds.	yds.	yds.
100 PSP	2.3	2.8	2.0	zero	-3.6	-16.2	-38.5
130 PSPCL	1.5	1.4	zero	-2.8	-7.0	-20.9	-43.3
130 BP	1.5	1.3	zero	-2.7	-6.8	-20.0	-41.1
130 SS	1.4	1.3	zero	-2.5	-6.5	-18.8	-38.2
150 SPCL	2.0	1.8	zero	-3.6	-9.4	-28.6	-61.2
140 SAFPSP	1.7	1.5	zero	-3.1	-7.8	-23.2	-48.0
140 PSPBT	1.6	1.4	zero	-2.7	-6.9	-20.1	-40.7
140 NBT	1.6	1.4	zero	-2.7	-6.9	-20.0	-40.3
150 NP	1.7	1.5	zero	-3.0	-7.5	-21.6	-43.6

.30-06 Springfield						
Index No.	Wt. (grs.)	Bullet Style	Primer No.	Barrel Length		
R30069	55	Pointed Soft Point, Accelerator	9 1/2	24"		
R30061	125	Pointed Soft Point	9 1/2	24"		
R30062	150	Pointed Soft Point Core-Lokt™	9 1/2	24"		
R30063	150	Bronze Pointú	9 1/2	24"		
PRSC3006C	150	Swiftú Sciroccoú	9 1/2	24"		
R3006B	165	Pointed Soft Point Core-Lokt™	9 1/2	24"		
R30064	180	Soft Point Core-Lokt™	9 1/2	24"		
R30065	180	Pointed Soft Point Core-Lokt™	9 1/2	24"		
R30066	180	Bronze Pointú	9 1/2	24"		
R30067	220	Soft Point Core-Lokt™	9 1/2	24"		
PRT3006A	150	Nosler™ Ballistic Tip™	9 1/2	24"		
PRB3006SA	165	Pointed Soft Point, Boat Tail	9 1/2	24"		
PRT3006B	165	Nosler™ Ballistic Tip™	9 1/2	24"		
RS3006A	180	Swiftú A-Frameú PSP	9 1/2	24"		
PRSC3006B	180	Swiftú Sciroccoú	9 1/2	24"		
PRP3006A	180	Nosler™ Partition™	9 1/2	24"		
Velocity (ft./sec.)						
Cartridge	Muzzle	100 yds.	200 yds.	300 yds.	400 yds.	500 yds.
55 PSP	4080	3484	2964	2499	2080	1706
125 PSP	3140	2780	2447	2138	1853	1595
150 PSPCL	2910	2617	2342	2083	1843	1622
150 BP	2910	2656	2416	2189	1974	1773
150 SS	2910	2696	2492	2298	2111	1934
165 PSPCL	2800	2534	2283	2047	1825	1621
180 SPCL	2700	2348	2023	1727	1466	1251
180 PSPCL	2700	2469	2250	2042	1846	1663
180 BP	2700	2485	2280	2084	1899	1725
220 SPCL	2410	2130	1870	1632	1422	1246
150 NBT	2910	2696	2492	2298	2112	1934
165 PSPBT	2800	2592	2394	2204	2023	1852
165 NBT	2800	2609	2426	2249	2080	1919
180 SAPSP	2700	2465	2243	2032	1833	1648
180 SS	2700	2522	2351	2186	2028	1878

180 NP	2700	2512	2332	2160	1995	1837	
Energy (ft.-lbs.)							
Cartridge	Muzzle	100 yds.	200 yds.	300 yds.	400 yds.	500 yds.	
55 PSP	2033	1482	1073	763	528	355	
125 PSP	2736	2145	1662	1269	953	706	
150 PSPCL	2820	2281	1827	1445	1131	876	
150 BP	2820	2349	1944	1596	1298	1047	
150 SS	2820	2421	2069	1758	1485	1246	
165 PSPCL	2872	2352	1909	1534	1220	963	
180 SPCL	2913	2203	1635	1192	859	625	
180 PSPCL	2913	2436	2023	1666	1362	1105	
180 BP	2913	2468	2077	1736	1441	1189	
220 SPCL	2837	2216	1708	1301	988	758	
150 NBT	2821	2422	2070	1769	1485	1247	
165 PSPBT	2872	2462	2100	1780	1500	1256	
165 NBT	2873	2494	2155	1854	1588	1350	
180 SAPSP	2913	2429	2010	1650	1343	1085	
180 SS	2913	2542	2208	1910	1644	1409	
180 NP	2913	2522	2174	1864	1590	1349	
Short-Range Trajectory *							
Cartridge	50 yds.	100 yds.	150 yds.	200 yds.	250 yds.	300 yds.	
55 PSP	-0.4	0.2	zero	-1.0	-3.0	-6.2	
125 PSP	-0.1	0.6	zero	-1.9	-5.2	-10.1	
150 PSPCL	0.2	0.7	zero	-2.2	-5.9	-11.4	
150 BP	0.2	0.7	zero	-2.0	-5.6	-10.8	
150 SS	0.1	0.7	zero	-2.0	-5.3	-10.2	
165 PSPCL	0.3	0.8	zero	-2.3	-6.3	-12.1	
180 SPCL	-0.1	zero	-1.5	-4.9	-10.3	-18.3	
180 PSPCL	-0.1	zero	-1.3	-4.2	-8.8	-15.4	
180 BP	-0.1	zero	-1.3	-4.2	-8.7	-15.0	
220 SPCL	0.1	zero	-2.0	-6.2	-12.9	-22.4	
150 NBT	0.1	0.7	zero	-2.0	-5.3	-10.2	
165 PSPBT	0.2	0.8	zero	-2.2	-5.8	-11.2	
165 NBT	0.2	0.8	zero	-2.1	-5.7	-10.9	
180 SAPSP	-0.1	zero	-1.3	-4.2	-8.9	-15.4	
180 SS	-0.1	zero	-1.3	-4.0	-8.3	-14.2	
180 NP	-0.1	zero	-1.3	-4.0	-8.4	-14.4	
Long Range Trajectory *							
Cartridge	100 yds.	150 yds.	200 yds.	250 yds.	300 yds.	400 yds.	500 yds.
55 PSP	1.4	1.8	1.4	zero	-2.6	-12.2	-30.0
125 PSP	1.5	1.4	zero	-2.8	-7.4	-22.4	-47.6
150 PSPCL	1.8	1.6	zero	-3.2	-8.2	-24.4	-50.9
150 BP	1.7	1.5	zero	-3.0	-7.7	-22.7	-46.6
150 SS	1.6	1.5	zero	-2.9	-7.3	-21.1	-42.3
165 PSPCL	2.0	1.7	zero	-3.4	-8.7	25.9	-53.2
180 SPCL	2.4	2.1	zero	-4.3	-11.0	33.8	-72.8
180 PSPCL	2.1	1.8	zero	-3.5	-9.0	-26.3	-54.0

180 BP	2.1	1.8	zero	-3.5	-8.8	-25.5	-52.0
220 SPCL	1.3	zero	-3.5	-9.5	-18.4	-46.4	-91.6
150 NBT	1.6	1.5	zero	-2.9	-7.3	-21.1	-42.8
165 PSPBT	1.8	1.6	zero	-3.1	-7.9	-23.0	-46.6
165 NBT	1.8	1.6	zero	-3.1	-7.7	-22.3	-45.0
180 SAPSP	2.1	1.8	zero	-3.6	-9.1	-26.6	-54.4
180 SS	2.0	1.7	zero	-3.3	-8.3	-23.9	-47.9
180 NP	2.0	1.7	zero	-3.3	-8.4	-24.3	-48.9